### **AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions and listings of claims in the application:

#### LISTING OF CLAIMS:

1. (currently amended): A face portion detecting apparatus comprising:

at least one illumination means for illuminating a face portion of a human being from different directions from each other;

photographing means for photographing the face portion which is illuminated by said illumination means;

illumination lighting control means for controlling turn-ON operation of said illumination means;

photographing control means for controlling said photographing means in synchronism with the turn-ON operation of said illumination means; and

face portion detecting means for removing a reflection image of an article having a luster reflection surface by employing at least one image which is acquired by said photographing means in synchronism with the turn-ON operation of said illumination means, whereby only a determined face portion is extracted[[.]];

### wherein:

said illumination lighting control means turns ON a plurality of illumination means in a continuous manner; and

while said face portion detecting means employs a plurality of images which are acquired by said photographing means in synchronism with the turn-ON operation of said illumination

means, said face portion detecting means removes a reflection image whose reflection position is moved among said plurality of images as the reflection image of the article having the luster reflection surface.

2. (original): A face portion detecting apparatus according to claim 1 wherein: said face portion corresponds to an eye portion, and

said face portion detecting means detects a retina reflection image which is formed by that the irradiation light of said illumination means is reflected on a retina of the human being.

- 3. (canceled).
- 4. (currently amended): A face portion detecting apparatus according to claim 2 comprising:

at least one illumination means for illuminating a face portion of a human being from different directions from each other;

photographing means for photographing the face portion which is illuminated by said illumination means;

illumination lighting control means for controlling turn-ON operation of said illumination means;

photographing control means for controlling said photographing means in synchronism with the turn-ON operation of said illumination means; and

face portion detecting means for removing a reflection image of an article having a luster reflection surface by employing at least one image which is acquired by said photographing means in synchronism with the turn-ON operation of said illumination means, whereby only a determined face portion is extracted;

wherein:

said face portion corresponds to an eye portion;

said face portion detecting means detects a retina reflection image which is formed by that the irradiation light of said illumination means is reflected on a retina of the human being;

both the illumination lighting control means and the photographing control means synchronize turn-ON operation of at least said one illumination means with the photographic operation of said photographing operation;

said illumination lighting control means turns ON at least one illumination means while said photographing means photographs one image; and

said face portion detecting means detects as the retina reflection image, such a reflection image which is present within a constant region among the images acquired by said photographing means, and an illuminance level of which is higher than, or equal to a predetermined value.

- 5. (original): A face portion detecting apparatus according to claim 1 wherein: at least a portion of said one illumination means is arranged within a range separated from an optical axis of said photographing means by a constant distance.
- 6. (original): A face portion detecting apparatus according to claim 1 wherein: at least one of said plurality of illumination means is arranged within a range separated from the optical axis of said photographing means by a constant distance.
- 7. (currently amended): A face portion detecting apparatus according to claim 2 comprising:

### AMENDMENT UNDER 37 C.F.R. § 1.111 U. S. Application No. 09/987,638

at least one illumination means for illuminating a face portion of a human being from different directions from each other;

photographing means for photographing the face portion which is illuminated by said illumination means;

illumination lighting control means for controlling turn-ON operation of said illumination means;

photographing control means for controlling said photographing means in synchronism with the turn-ON operation of said illumination means; and

face portion detecting means for removing a reflection image of an article having a luster reflection surface by employing at least one image which is acquired by said photographing means in synchronism with the turn-ON operation of said illumination means, whereby only a determined face portion is extracted;

wherein:

said face portion corresponds to an eye portion;

said face portion detecting means detects a retina reflection image which is formed by that the irradiation light of said illumination means is reflected on a retina of the human being;

at least a portion of said one illumination means is arranged within a range separated from the optical axis of said photographing means by a constant distance, and said illumination means owns a predetermined shape;

said illumination lighting control means turns ON said illumination means while one image is photographed; and

## AMENDMENT UNDER 37 C.F.R. § 1.111 U. S. Application No. 09/987,638

said face portion detecting means detects as the retina reflection image, such a reflection image which is present within constant region among the images acquired by said photographing means, and the luminance level of which is higher than, or equal to a predetermined value, and furthermore, removes such a reflection image having a shape identical to said predetermined shape of said illumination means as the reflection image of the article having the luster reflection surface.

8. (currently amended): A face portion detecting apparatus according to claim 2 comprising:

at least one illumination means for illuminating a face portion of a human being from different directions from each other;

photographing means for photographing the face portion which is illuminated by said illumination means;

illumination lighting control means for controlling turn-ON operation of said illumination means;

photographing control means for controlling said photographing means in synchronism with the turn-ON operation of said illumination means; and

face portion detecting means for removing a reflection image of an article having a luster reflection surface by employing at least one image which is acquired by said photographing means in synchronism with the turn-ON operation of said illumination means, whereby only a determined face portion is extracted;

wherein:

said face portion corresponds to an eye portion;

said face portion detecting means detects a retina reflection image which is formed by that the irradiation light of said illumination means is reflected on a retina of the human being;

at least one of said plurality of illumination means is arranged within a range separated from an optical axis of said photographing means by a constant distance, and said plurality of illumination means are arranged in such a manner that said plural illumination means constitute a predetermined shape;

said illumination lighting control means turns ON said plurality of illumination means while one image is photographed; and

said face portion detecting means detects as the retina reflection image, such a reflection image which is present within a constant region among the images acquired by said photographing means, and the luminance level of which is higher than, or equal to a predetermined value, and furthermore, removes such a reflection image having a shape identical to said predetermined shape of said plurality of illumination means as the reflection image of the article having the luster reflection surface.

- 9. (original): A face portion detecting apparatus according to claim 7 wherein: said predetermined shape of the illumination means is a straight-line shape.
- 10. (original): A face portion detecting apparatus according to claim 7 wherein: said predetermined shape of the illumination means is a coaxial shape with respect to the optical axis of said photographing means.
  - 11. (original): A face portion detecting apparatus according to claim 1 wherein: the irradiation light of said illumination means corresponds to near infrared rays.
  - 12. (original): A face portion detecting apparatus according to claim 1 wherein:

# AMENDMENT UNDER 37 C.F.R. § 1.111 U. S. Application No. 09/987,638

the irradiation light of said illumination means corresponds to infrared rays.